



**E·A·R™**  
Hearing Protection

## Push-Ins™ Earplugs

- No roll-down required
- Slow-recovery foam
- E-A-Rfit™ testable
- Available with or without cord

318-1000 uncorded

318-1001 corded



**Noise  
Reduction  
Rating**

**28** Decibels

(When used as directed)

THE RANGE OF NOISE REDUCTION RATINGS  
FOR EXISTING HEARING PROTECTORS  
IS APPROXIMATELY 0 TO 30  
(HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)

3M Company,  
St Paul, MN

Push-Ins

Federal law prohibits  
removal of this label  
prior to purchase



LABEL REQUIRED BY  
U.S. E.P.A.  
REGULATION  
40 CFR PART 211  
SUBPART B

3M strongly recommends fit testing of hearing protectors. Research suggests that many users will receive less noise reduction than indicated by the NRR due to variation in hearing protector fit, fitting skill and motivation of the user. If the NRR is used to estimate typical workplace protection, 3M recommends that the NRR be reduced by 50% or in accordance with applicable regulations.

**E·A·Rfit™**  
VALIDATION SYSTEM

Testable with the 3M™ E-A-Rfit™  
Dual-Ear Validation System  
Visit [www.3M.com/earfit](http://www.3M.com/earfit)

To purchase, contact your local PPE distributor.